


IMMERSION RTD'S

TEMPERATURE RANGE: -58°F to 752°F (-50°C to 400°C)



SPECIFICATIONS

RTD Element


Type: Platinum, Thin Film
 Resistance @ 0° C: 100 OHMS
 Temperature Coefficient of Resistance: .00385
 Sheath Material: 316 Stainless Steel
 Insulation: Fiberglass

Lead Wire


Conductor Size: 24 Gauge Stranded
 Conductor Material: Nickel Plated Copper
 Insulation: Fiberglass or Teflon(FEP)
 Armor: Stainless Steel, Flexible

Connectors

Body Material: Thermoplastic
 Polarized Pins
 Spring Loaded Inserts
 Maximum Temperature Limit: 390°F (200°C)



DETAIL A



ORDERING CODE

| CODE | SHEATH DIAMETER | AVAILABILITY (W=WIRES, T=TOTAL) | | | | | |
|------|-----------------|---------------------------------|----|----|--------|--------|--------|
| | | SINGLE | | | DUPLEX | | |
| | | 2W | 3W | 4W | 2W(4T) | 3W(6T) | 4W(8T) |
| 18 | 1/8" (3.2mm) | ● | ● | ● | ● | ● | ● |
| 316 | 3/16" (4.8mm) | ● | ● | ● | ● | ● | ● |
| 14 | 1/4" (6.4mm) | ● | ● | ● | ● | ● | ● |

| CODE | ACCURACY (ASTM E1137) |
|------|-----------------------|
| | CLASS B (LEAVE BLANK) |
| CLA | CLASS A |

| CODE | IMMERSION LENGTH |
|------|-----------------------------|
| | IN INCHES (28" MAX. LENGTH) |

| CODE | LEAD LENGTH |
|------|-------------|
| | (IN INCHES) |

| CODE | SYSTEM |
|------|-----------------------|
| 2W | 2 WIRE (4 DUPLEX) |
| | 3 WIRE (LEAVE BLANK)* |
| 4W | 4 WIRE |

*Single or Duplex

D - RTD - 14 - MT - 18 - 96 - 2 - C / C1 - CLA - 2W

| CODE | STRUCTURE |
|------|----------------------|
| | SINGLE (LEAVE BLANK) |
| D | DUPLEX |

| CODE | LEAD WIRE INSULATION |
|------|----------------------------|
| 2 | FIBERGLASS W/ARMOR OVERALL |
| 8 | TEFLON W/ARMOR OVERALL |

| CODE | TERMINATION |
|------|--------------------------|
| A | BARE ENDS (NOTE 1) |
| T | STANDARD SIZE 3 PIN PLUG |
| L | STANDARD SIZE 2 PIN PLUG |
| C | STANDARD SIZE 4 PIN PLUG |
| H | MINIATURE 2 PIN PLUG |
| H3 | MINIATURE 3 PIN PLUG |
| T3 | STANDARD SIZE 6 PIN PLUG |

| CODE | MATING CONNECTOR (OMIT IF NOT ORDERED) |
|------|--|
| T1 | STANDARD SIZE 3 PIN JACK |
| N | STANDARD SIZE 2 PIN JACK |
| C1 | STANDARD SIZE 4 PIN JACK |
| K | MINIATURE 2 PIN JACK |
| K3 | MINIATURE 3 PIN JACK |
| TT3 | STANDARD SIZE 6 PIN JACK |

Notes:

- (1) Available with spade lugs, replace "A" with "LG".
- (2) For an item that does not fall within the catalog description an (SP) can be added to the ordering code as part of a custom construction.



TEMPERATURE MEASUREMENT DESIGNER'S GUIDE
 WWW.THERMO-ELECTRIC-DIRECT.COM

SECTION IMRD

TYPE "MT"

IMMERSION RTD'S with ARMORED LEAD WIRE
 SINGLE & DUPLEX CONSTRUCTION

The information contained hereon shall be considered the sole property of Thermo Electric Company, Inc. The recipient thereof agrees not to disclose or reproduce said information to parties outside the recipient's organization without the written permission of Thermo Electric.

Doc. No.: TE-CO010109-IMRD-100