


IMMERSION RTD'S

TEMPERATURE RANGE: -292°F to 1202°F (-180°C to 650°C)




SPECIFICATIONS

RTD Element

Type: Platinum, Wire Wound
 Resistance @ 0° C: 100 OHMS
 Temperature Coefficient of Resistance: .00385
 Sheath Material: Inconel 600
 Insulation: Hard Packed MgO

Lead Wire

Conductor Size: 24 Gauge Stranded
 Conductor Material: Nickel Plated Copper
 Insulation: Fiberglass or Teflon(FEP)
 Armor: Stainless Steel, Flexible



DETAIL A

Connectors

Body Material: Thermoplastic
 Polarized Pins
 Spring Loaded Inserts
 Maximum Temperature Limit: 390°F (200°C)

ORDERING CODE

CODE	SHEATH DIAMETER	AVAILABILITY (W=WIRES, T=TOTAL)					
		SINGLE			DUPLEX		
		2W	3W	4W	2W(4T)	3W(6T)	4W(8T)
316	3/16" (4.8mm)	●	●	●	●	●	●
14	1/4" (6.4mm)	●	●	●	●	●	●

CODE	IMMERSION LENGTH IN INCHES
14	14
18	18
96	96

CODE	LEAD LENGTH IN INCHES
2	2

CODE	SYSTEM
2W	2 WIRE (4 DUPLEX)
3W	3 WIRE (LEAVE BLANK)*
4W	4 WIRE (SINGLE ONLY)

*Single or Duplex


D - RTD - 14 - HT - 18 - 96 - 2 - C / C1

CODE	STRUCTURE
	SINGLE (LEAVE BLANK)
D	DUPLEX

CODE	LEAD WIRE INSULATION
2	FIBERGLASS W/ARMOR OVERALL
8	TEFLON W/ARMOR OVERALL

CODE	TERMINATION
A	BARE ENDS (NOTE 1)
T	STANDARD SIZE 3 PIN PLUG
Tx	EXTENDED LIMITS 3 PIN PLUG
L	STANDARD SIZE 2 PIN PLUG
C	STANDARD SIZE 4 PIN PLUG
H	MINIATURE 2 PIN PLUG
H3	MINIATURE 3 PIN PLUG
T3	STANDARD SIZE 6 PIN PLUG

CODE	MATING CONNECTOR (OMIT IF NOT ORDERED)
T1	STANDARD SIZE 3 PIN JACK
T1x	EXTENDED LIMITS 3 PIN JACK
N	STANDARD SIZE 2 PIN JACK
C1	STANDARD SIZE 4 PIN JACK
K	MINIATURE 2 PIN JACK
K3	MINIATURE 3 PIN JACK
TT3	STANDARD SIZE 6 PIN JACK



Notes:

- (1) Available with spade lugs, replace "A" with "LG".
- (2) Sheath may be bent to up to a diameter of twice the radius from 2" past tip on single and 3" on duplex.
- (3) Type "HT" not available in Class A accuracy.
- (4) For an item that does not fall within the catalog description an (SP) can be added to the ordering code as part of a custom construction.



SECTION IMRD

TYPE "HT"

IMMERSION RTD'S with ARMORED LEAD WIRE SINGLE & DUPLEX CONSTRUCTION

The information contained hereon shall be considered the sole property of Thermo Electric Company, Inc. The recipient thereof agrees not to disclose or reproduce said information to parties outside the recipient's organization without the written permission of Thermo Electric.