
INDUSTRIAL THERMOCOUPLES TYPE XD TYPE A **THERMO** 3.44Ø EXPLOSION PROOF ALUMINUM HEAD STANDARD FEATURES Chemically Resistant Painted Cast Aluminum WEATHERPROOF HEAVY DUTY CAST IRON HEAD Body & Cover Stainless Steel Link Chain STANDARD FEATURES Neoprene O-ring Internal, External Ground Screw Cast Iron Body & Cover with Heat Resistant Aluminum Paint Available Tube Openings: 1/2", 3/4"NPT Available Conduit Openings: 1/2" with reducer, Galvanized Jack Chain Fiber Gasket 3/4"NPT, M20 X 1.5, (Dual Conduit Openings) Available Tube Openings: 1/2", 3/4", 1"NPT COMPLIANCE Available Conduit Openings: 1/2" with reducer, ATEX Approved EEx d IIC T6 CSA & FM Approved for Optional Neoprene gasket: Class 1, Division 1, Groups A, B, C, & D Class 2, Division 2, Groups E, F & G Add "OR" to Code (A-OR) 3.88 NEMA-4, -4X, IP66 TYPE AX




POLYPROPYLENE HEAD

STANDARD FEATURES Black Polypropylene Body & Cover Stainless Steel Ball Chain

Rubber Gasket Available Tube Openings: 1/2", 3/4", 1"NPT Available Conduit Openings: 1/2" with PVC reducer, 3/4"NPT

CODE	HEAD TYPE	
	SERVICE	MATERIAL
Α	WEATHERPROOF, HEAVY DUTY	CAST IRON
XD	EXPLOSION PROOF	ALUMINUM
L	LIGHT WEIGHT PLASTIC	POLYPROPYLENE
AX	LARGE DEVICE	ALUMINUM



4.66 3.66

LARGE DEVICE ATEX APPROVED ALUMINUM HEAD

STANDARD FEATURES


Epoxy Coated Blue Cast Aluminum Body & Cover Stainless Steel Ball Chain

Neoprene O-ring Internal, External Ground Screw

Available Tube Openings: 1/2", 3/4"NPT Available Conduit Openings: 1/2", 3/4"NPT, M20 x 1.5

COMPLIANCE ATEX Approved EEx d IIC T6

CSA & FM approval Pending



THERMO ELECTRIC

SECTION INTO

CONNECTION HEADS

The information contained hereon shall be considered the sole property of Thermo Electric Company, Inc. The recipient thereof agrees not to disclose or reproduce said information to parties outside the recipients organization without the written permission of Thermo Electric.

Doc. No.: TE-CO010109-INTC-270